



BARREL MOUNTED SPRAYER

The BMS75 and BMS95 mix and spray water based curing and sealing compounds and form release agents for concrete applications. The BMS75 features a 7.5 gpm roller pump and will handle up to 25% solids efficiently. The BMS95 utilizes a 9.5 gpm diaphragm pump for handling heavier particulate loads to 35%.

Both sprayers are housed in an extra wide, heavy duty protective cage. The sprayers are easily locked to a 55 gallon drum or can be used in conjunction with the Easy Load Cart. No lifting is required... heavy 55 gallon drums are simply rolled onto the tilt bed of the Easy Load Cart and secured with a winch strap. The cart rolls on pneumatic tires and rubber castors for use on green concrete without damaging the slab.



OPTIONS

- Pressure Gauge (BMS75 only - standard on BMS95)
- 9' Spray Wand
- 25' Hose Assembly
- 50' Hose Assembly
- 100' Hose Assembly
- Spray Tip Kit (2 each fine, medium and heavy tips)
- Drum Cart



BARREL MOUNTED SPRAYERS

CONTACT INFORMATION

MBW Inc.
250 Hartford Road, P.O. Box 440
Slinger, Wisconsin 53086-0440
USA

800-678-5237 • 262-644-5234
Fax: 262-644-5169

E-mail: mbw@mbw.com
Website: www.mbw.com

SPECIFICATIONS	BMS75 WITH 25' HOSE & WAND	BMS95 WITH 25' HOSE & WAND
Pump	Roller	Diaphragm
Solids Content (high efficiency/max. rating)	25%/30%	35%
Maximum Flow	7.5 gpm (28.3 lpm)	9.5 gpm (36 lpm)
Maximum Pressure	300 psi (20.7 bar)	550 psi (38 bar)
Adjustable Pressure Settings	Yes	Yes
Standard Operating Pressure	100 psi (6.8 bar)	100 psi (6.8 bar)
Weight	95 lbs (43 kg)	115 lbs (52 kg)
Dimensions (L x W x H)	27 x 16 x 17 in (66 x 41 x 43 cm)	27 x 16 x 17 in (66 x 41 x 43 cm)
Engine	Honda 4 hp (2.9 kw)	Honda 5.5 hp (4.0 kw)
Quick Disconnect Fittings	Yes	Yes

() Metric Measurements.
Specifications subject to change without notice.